



Microsersion® 1226XF-50

A water based dispersion of a highly engineered HDPE/ceramic/nanoceramic composite for abrasion resistance and lubricity

Features and Benefits

- Convenient, ready-to-use, pourable water based wax dispersion
- HDPE composite reinforced with hard, inert ceramic microspheres and nanoceramic platelets
- Improved Taber abrasion resistance when compared to PE/PTFE additives
- Provides slip and lubricity
- Ideal for can and container coatings; 21CFR 175.300 approved
- Effective replacement for PTFE additives

Dry Wax ID

PolyGlide 1226XF

Recommended Addition Levels

2.0-5.0% (on total formula weight)

Systems and Applications

Water based coatings and inks. Industrial coatings (including plastic and metal); stains, sealers and varnishes; wood coatings; printing inks and OPV's (including flexo and gravure); can, container, and coil coatings; rubber additives.

Typical Properties*

Microsersion 1226XF-50

| | |
|------------------------------------|--------------|
| Wax Solids | 54.2 – 58.2% |
| Viscosity @ 25 °C (cP) | 0.00 |
| pH | 9.0 - 10.5 |
| Density @ 25 °C (g/cc) | 0.99 |
| Wax Mean Particle Size (µm) | 0.00 |
| NPIRI Grind | 1.0 - 2.0 |

Dec-25